Barton Series Linear High Bay



Energy-Efficient Lighting with Frosted Optical PC Cover for Uniform Luminance

Features

- Heavy Duty Extruded Aluminum 6063 Housing with Outstanding Heat Dissipation Performance
- Extremely Energy Efficient—Up to Real 150 lm/w
- IP65 and IK10 Protection for Industrial Environments

Options

- 1–10V Dimmable and DALI Driver
- Microwave Motion Sensor
- Emergency Power Supply
- Zigbee Control

Certificates

• American Market: UL, DLC Premium, cUL

(h) 🏟 (h) 🌚 🖙 (E CB 🕑 🕅

Watts	lm/ watt	Lumen Output	Beam Angle	CRI	Current	Color Temps	UGR	L70 (Hrs)	Finish	Mount	Dimensions	IP Protection	Options
150	150	22500	120	>70	120-277 or 480v		<27	100,000	Silver	Suspended w/aircraft cable (incl)	36" long		 Dimmable Motion sensors Emergency power Wireless control

Specifications



Kansas City Location

2930 Terrace St Kansas City MO 64108 **TEL 913-912-3760**

leddirectgroup.com

Come visit our showroom featuring more than 50 fixtures on display.

All statements, technical information and recommendations contained in this document are based on information and tests we believe to be reliable. The accuracy or completeness thereof is not guaranteed. We reserve the right to revise or update this document without notice. Since the conditions of use are outside our control, the purchaser should determine the suitability of the product for its intended use and assumes all risk and liability whatsoever in connection therewith.